# U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

# **ELEVATION CERTIFICATE**

Important: Read the instructions on pages 1-9.

25/6

OMB No. 1660-0008

Expiration Date: July 31, 2015

SECTION A - PROPERTY INFORMATION					SIURAKOE COMBANYIUSE:
A1. Building Owner's Name MICHAEL SILBERMAN				I7/ēllēy N	nalcins especial (Company)
A2. Building Street Address (including Apt., Unit, Su #3 SOUTH 25 <sup>TH</sup> AVENUE	ite, and/or Bldg. No	o.) or P.O. Route and	I Box No.	(Cloimpia)	y NAIC Number:
City BOROUGH OF LONGPORT		State NJ ZIP	Code 08403		İ
A3. Property Description (Lot and Block Numbers, TBLOCK 25 LOT 6	ax Parcel Number,	Legal Description, e	tc.)		
B1. NFIP Community Name & Community Number	Horizontal I e Certificate is being 1200 rawlspace t grade 7 1328 No FLOOD INSURA	Datum: NAD 19.  ng used to obtain floo  A9.  sq ft  sq in  ANCE RATE MAF	DATE OF THE PROPERTY OF THE P	ached gara it flood ope adjacent g d openings enings?	age <u>N/A</u> sq ft snings in the attached garage brade <u>N/A</u> in A9.b <u>N/A</u> sq in ☐ Yes ⊠ No
BOROUGH OF LONGPORT 345302	ATLAN	TIC COUNTY		NJ	
	M Index Date dex Printed	B7. FIRM Pane Effective/Revised D 08/15/1983			ase Flood Elevation(s) (Zone O, use base flood depth) 10***
☐ FIS Profile ☐ FIRM ☐ Committee Co	on the second second second		Other/Source: Protected Area (OPA)?		□ Yes ⊠ No
SECTION C - BU	JILDING ELEVA	TION INFORMAT	ION (SURVEY REQUI	RED)	
<ol> <li>Building elevations are based on:            Const          *A new Elevation Certificate will be required when</li> </ol>	ruction Drawings*	☐ Building	Under Construction*		ished Construction
Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private     Indicate elevation datum used for the elevations in Datum used for building elevations must be the sar	, VE, V1–V30, V (windlern No. In Puert Vertic items a) through h	vith BFE), AR, AR/A to Rico only, enter m cal Datum: <u>NGVD 19</u> ) below. ☑ NGVD 1	, AR/AE, AR/A1–A30, AR eters. <u>929</u> 929 □ NAVD 1988 □ 0	Other/Sour	.: ce:
Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in	, VE, V1–V30, V (w in Item A7. In Puert Vertic items a) through h me as that used for	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	, AR/AE, AR/A1–A30, AR eters. <u>929</u> 929 □ NAVD 1988 □ C	Other/Sour	ce:surement used.
Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: <u>private</u> Indicate elevation datum used for the elevations in Datum used for building elevations must be the sail	, VE, V1–V30, V (w in Item A7. In Puert Vertic items a) through h me as that used for	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	, AR/AE, AR/A1–A30, AR eters. <u>929</u> 929 □ NAVD 1988 □ 0	Other/Sour	.: ce:
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sa a) Top of bottom floor (including basement, crawls b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb	, VE, V1–V30, V (win Item A7. In Puert Vertic items a) through hime as that used for pace, or enclosure	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	AR/AE, AR/A1–A30, AR leters. <u>929</u> 929 □ NAVD 1988 □ C Chec <u>7.1</u> 13.4 N/A.	Other/Sour k the meas feet feet feet	ce:surement used.
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sa a) Top of bottom floor (including basement, crawls b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab)	, VE, V1–V30, V (win Item A7. In Puertic Vertic items a) through hime as that used for pace, or enclosure er (V Zones only)	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	AR/AE, AR/A1–A30, AR leters. <u>929</u> 929 □ NAVD 1988 □ C Chec <u>7.1</u> 13.4 N/A. N/A.	Other/Source  k the meas feet feet feet feet feet	ce:surement used.    meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sail a) Top of bottom floor (including basement, crawls; b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Control of the support of the suppo	, VE, V1–V30, V (with Item A7. In Puertic Vertic items a) through hime as that used for pace, or enclosure er (V Zones only) vicing the building nments)	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	AR/AE, AR/A1–A30, AR leters. 929 929 NAVD 1988 Chec 7.1 13.4 N/A. N/A. 11.2****	Other/Source k the meas feet feet feet feet feet feet	ce: surement used.    meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sa a) Top of bottom floor (including basement, crawls b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Corf) Lowest adjacent (finished) grade next to building	y VE, V1–V30, V (with Item A7. In Puertic Vertic items a) through hime as that used for pace, or enclosure er (V Zones only) vicing the building nments)	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 rthe BFE.	AR/AE, AR/A1–A30, AR leters. 929 929 NAVD 1988 Chec 7.1 13.4 N/A. N/A. 11.2**** 6.9	Other/Source k the meas limited feet	ce: surement used.    meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sail a) Top of bottom floor (including basement, crawls; b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Control of the support of the suppo	y VE, V1–V30, V (with Item A7. In Puertic Vertic items a) through hyme as that used for pace, or enclosure er (V Zones only) vicing the building naments) g (LAG) g (HAG)	vith BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. ☑ NGVD 1 r the BFE. floor)	AR/AE, AR/A1–A30, AR eters. 929 929 NAVD 1988 Chec 7.1 13.4 N/A. N/A. 11.2**** 6.9 7.6	Other/Source k the meas feet feet feet feet feet feet	ce: surement used.    meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the said a) Top of bottom floor (including basement, crawls; b) Top of the next higher floor c) Bottom of the lowest horizontal structural membing d) Attached garage (top of slab)  e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Conf. Lowest adjacent (finished) grade next to building g) Highest adjacent grade at lowest elevation of decent process.	, VE, V1–V30, V (with lem A7. In Puerto Vertice items a) through hime as that used for pace, or enclosure er (V Zones only) vicing the building naments) g (LAG) g (HAG) ck or stairs, including	with BFE), AR, AR/A, to Rico only, enter metal Datum: NGVD 19 ) below. NGVD 1 r the BFE.  floor)	AR/AE, AR/A1–A30, AR eters. 929 929 NAVD 1988 Chec 7.1 13.4 N/A. N/A. 11.2**** 6.9 7.6	Other/Source k the meas left feet	ce: surement used.    meters   meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sail a) Top of bottom floor (including basement, crawls b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Conf) Lowest adjacent (finished) grade next to building g) Highest adjacent (finished) grade next to building h) Lowest adjacent grade at lowest elevation of decent services adjacent grade at lowest elevation of decent services in the information on this Certifical I understand that any false statement may be punishated.  Check here if comments are provided on back of Check here if attachments.	, VE, V1–V30, V (with Item A7. In Puert Vertice items a) through hime as that used for pace, or enclosure or (V Zones only) vicing the building naments) or (LAG) or stairs, including the part of the pack or stairs, including surveyor, engineer, pate represents my ble by fine or imprisorm. Were lat	with BFE), AR, AR/A, to Rico only, enter me cal Datum: NGVD 19 below. NGVD 1 reference NGVD	AR/AE, AR/A1–A30, AR eters.  229 929 □ NAVD 1988 □ C  Chec  7.1 13.4 N/A. N/A. 11.2****  6.9 7.6 N/A.  HITECT CERTIFICATION  ted by law to certify elevation and available. S. Code, Section 1001. in Section A provided by  ☑ Yes □ No	Continuity of the continuity o	ce: surement used.    meters   meters   meters   meters   meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sail a) Top of bottom floor (including basement, crawls; b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Conf. Lowest adjacent (finished) grade next to building g) Highest adjacent (finished) grade next to building h) Lowest adjacent grade at lowest elevation of decent services adjacent grade at lowest elevation of decent services in the certification is to be signed and sealed by a land sinformation. I certify that the information on this Certification is to be statement may be punishated.  Check here if comments are provided on back of	, VE, V1–V30, V (with Item A7. In Puert Vertice items a) through hime as that used for pace, or enclosure or (V Zones only) vicing the building naments) or (LAG) or stairs, including the part of the pack or stairs, including surveyor, engineer, pate represents my ble by fine or imprisorm. Were lat	with BFE), AR, AR/A, to Rico only, enter me cal Datum: NGVD 19 below. NGVD 1 reference NGVD	AR/AE, AR/A1–A30, AR eters.  229 929 □ NAVD 1988 □ C  Chec  7.1 13.4 N/A. N/A. 11.2****  6.9 7.6 N/A.  HITECT CERTIFICATIons the data available. S. Code, Section 1001. in Section A provided by	Continuity of the continuity o	ce: surement used.    meters   meters   meters   meters   meters   meters   meters   meters   meters   meters
22. Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sa a) Top of bottom floor (including basement, crawls b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Conf) Lowest adjacent (finished) grade next to building g) Highest adjacent (finished) grade next to building h) Lowest adjacent grade at lowest elevation of definition is to be signed and sealed by a land sinformation. I certify that the information on this Certific I understand that any false statement may be punishated.  Check here if comments are provided on back of Check here if attachments.  Certifier's Name Paul M. Koelling, PLS, CFM  Title Licensed Land Surveyor Companion in the companion of the compani	, VE, V1–V30, V (with Item A7. In Puerto Vertice items a) through hime as that used for pace, or enclosure er (V Zones only) vicing the building naments) g (LAG) g (HAG) ck or stairs, including surveyor, engineer, pate represents my ble by fine or imprise form. Were lated it with the surveyor of the s	with BFE), AR, AR/A, to Rico only, enter mental Datum: NGVD 15 or the BFE.  In the BFE.  INDEER, OR ARCH, or architect authorize best efforts to interpolations and longitude at land surveyor?  License Nur Coelling & Associates	AR/AE, AR/A1–A30, AR eters.  229 929 □ NAVD 1988 □ C  Chec  7.1 13.4 N/A. N/A. 11.2****  6.9 7.6 N/A.  HITECT CERTIFICATION  Led by law to certify elevation the data available.  S. Code, Section 1001.  in Section A provided by  □ Yes □ No  Inber NJ24GS 04328800  6, LLC	Continuity of the continuity o	ce: surement used.    meters   meters   meters   meters   meters   meters   meters   meters   meters   meters
Elevations – Zones A1–A30, AE, AH, A (with BFE) below according to the building diagram specified Benchmark Utilized: private Indicate elevation datum used for the elevations in Datum used for building elevations must be the sate a) Top of bottom floor (including basement, crawls) b) Top of the next higher floor c) Bottom of the lowest horizontal structural memb d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment ser (Describe type of equipment and location in Conf) Lowest adjacent (finished) grade next to building g) Highest adjacent (finished) grade next to building h) Lowest adjacent grade at lowest elevation of decent sertification is to be signed and sealed by a land a information. I certify that the information on this Certific I understand that any false statement may be punished.  ☐ Check here if comments are provided on back of Check here if attachments.  Certifier's Name Paul M. Koelling, PLS, CFM	, VE, V1–V30, V (with Item A7. In Puerto Vertice items a) through hime as that used for pace, or enclosure er (V Zones only) vicing the building naments) by (LAG) go (HAG) ck or stairs, including surveyor, engineer, pate represents my ble by fine or imprisate form. Were laid licensed by Name Paul H. Keywood	with BFE), AR, AR/A, to Rico only, enter mental Datum: NGVD 19 below. NGVD 19 rethe BFE.  floor)  INEER, OR ARCH or architect authorize best efforts to interpersonment under 18 U titude and longitude di land surveyor?  License Nur  Coelling & Associates  State NJ	AR/AE, AR/A1–A30, AR eters.  229 929 □ NAVD 1988 □ C  Chec  7.1 13.4 N/A. N/A. 11.2**** 6.9 7.6 N/A.  HITECT CERTIFICATIOn the data available. S. Code, Section 1001. in Section A provided by Import NJ24GS 04328800	Continuity of the continuity o	ce: surement used.    meters   meters   meters   meters   meters   meters   meters   meters   meters   meters

IMPORTANT: In these spaces, co	opy the corresponding information fro	om Section A.		FOR INSURANCE COMPANY USE	
Building Street Address (including Apt., #3 SOUTH 25TH AVENUE	, Unit, Suite, and/or Bldg. No.) or P.O. Route	and Box No.		Policy Number:	
City BOROUGH OF LONGPORT	State NJ	ZIP Code 084	403	Company NAIC Number:	
SECTION	D – SURVEYOR, ENGINEER, OR ARC	HITECT CERTI	IFICATION (C	ONTINUED)	
Copy both sides of this Elevation Certif	icate for (1) community official, (2) insurance	agent/company, a	and (3) building	owner.	
***B8 & B9.) FEMA Flood Hazard Res ****C2e.) Air unit elevtion is 15.9, ductw	10 engineered for 200 square inches of net an sources Map Zone "AE"Base Flood Elevat work elevation is 11.2, furance elev. is 14.7, w	ion 9 ft. (NAVD88	b) converted = 1	10.3 ft. (NGVD29)	
SECTION E - BUILDING ELEV	VATION INFORMATION (SURVEY NOT	REQUIRED) F	OR ZONE AC	O AND ZONE A (WITHOUT BFE)	
and C. For Items E1–E4, use natural g E1. Provide elevation information for grade (HAG) and the lowest adja a) Top of bottom floor (including l b) Top of bottom floor (including l	basement, crawlspace, or enclosure) is basement, crawlspace, or enclosure) is permanent flood openings provided in Section	sed. In Puerto Ricco s to show whethe  feed. In Puerto Ricco s to show whethe feed. If the second se	o only, enter me or the elevation is eet	eters. s above or below the highest adjacent  □ above or □ below the HAG. □ above or □ below the LAG.  –9 of Instructions), the next higher floor	
<ul> <li>E3. Attached garage (top of slab) is</li> <li>E4. Top of platform of machinery and</li> <li>E5. Zone AO only: If no flood depth rordinance?  Yes  No </li> </ul>	Nor equipment servicing the building is number is available, is the top of the bottom for the bottom for the bottom for the local official must certify this	ove or	the HAG. meters accordance with tection G.	above or  below the HAG. the community's floodplain management	
	F – PROPERTY OWNER (OR OWNER				
or Zone AO must sign here. The statem	ted representative who completes Sections A ments in Sections A, B, and E are correct to the	, B, and E for Zon e best of my knov	ie A (without a F wledge.	FEMA-issued or community-issued BFE)	
Property Owner's or Owner's Authorize	City		State	ZIP Code	
Address	Date			Telephone	
Signature	Date			None .	
Comments					
				☐ Check here if attachment	
	SECTION G - COMMUNITY INFO				
f this Elevation Certificate. Complete the	or ordinance to administer the community's flo applicable item(s) and sign below. Check the r as taken from other documentation that has	neasurement used been signed and s	d in Items G8–G sealed by a licer	i10. In Puerto Rico only, enter meters.  nsed surveyor, engineer, or architect who	
is authorized by law to certify et al. A community official completed	elevation information. (Indicate the source and Section E for a building located in Zone A (vois Section E for a building located in Zone A (vois Section E for community floodp	d date of the eleven vithout a FEMA-is	ation data in the sued or commu	e Comments area below.)	
G3. The following information (Item G4. Permit Number	G5. Date Permit Issued			empliance/Occupancy Issued	
G4. Fellilit Nullibel	Go. Bate Ferrit 1994ed				
<ul> <li>This permit has been issued for:</li> <li>Elevation of as-built lowest floor (inc.)</li> <li>BFE or (in Zone AO) depth of flood</li> <li>Community's design flood elevation</li> </ul>	ing at the building site:	Improvement   feet   feet   feet	☐ meters ☐ meters ☐ meters	Datum Datum Datum	
Local Official's Name		Title			
20001 01110101 0 7101110					
		Telephone			
	-	Telephone Date			
Community Name				☐ Check here if attachment	

# **Building Photographs**

Building Street Address (including Apt., Unit, Suite, and/or Bldg.) No. or P.O. Route and Box No.

State
Longport

Continuation Page

For Insurance Company Use:

Policy Number

Company NAIC Number

Company NAIC Number

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View."





Front View - Date of Photograph: (See Photo Stamp)

Rear View - Date of Photograph: (See Photo Stamp)





Right Side View - Date of Photograph: (See Photo Stamp)

Vent View - Date of Photograph: (See Photo Stamp)



# **ICC-ES Evaluation Report**

**ESR-2074** 

Reissued February 1, 2009

This report is subject to re-examination in two years.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 10—SPECIALTIES Section: 10230—Vents

REPORT HOLDER:

SMART VENT<sup>9</sup>, INC. 450 ANDBRO DRIVE, SUITE 2B PITMAN, NEW JERSEY 08071 (856) 307-1468 www.smartvent.com eval@smartvent.com

#### **EVALUATION SUBJECT:**

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS:
FLOODVENT™ MODEL #1540-520; FLOODVENT™
STACKING MODEL #1540-521; SMARTVENT™ MODEL
#1540-510; SMARTVENT™ STACKING MODEL #1540-511;
WOOD WALL FLOOD MODEL #1540-570; WOOD WALL
FLOOD OVERHEAD DOOR MODEL #1540-524;
SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

## 1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- 2006 International Residential Code® (IRC)

## Properties evaluated:

- Physical operation
- Water flow

# 2.0 USES

The Smart Vent<sup>®</sup> units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

#### 3.0 DESCRIPTION

## 3.1 General:

When subjected to pressure from rising water, the Smart Vent<sup>®</sup> AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 78 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

# 3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

#### 3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

#### 3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

# 4.0 INSTALLATION

SmartVENT<sup>®</sup> and FloodVENT<sup>™</sup> are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to